Specifications — IRL 20

Control/remote — IR repeater

IR controller module	Extron IR remote controls only
IR output carrier frequency	38 kHz

NOTE *Use the IRL 20 with Extron products only.*

General

External power supply	12 VDC, regulated; from an Extron MediaLink Controller, MediaLink Switcher, System 5 IP, AVT 100, or an external power supply
Power input requirements	12 VDC, 50 mA
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Rack mount	No
Enclosure type	Plastic
Enclosure dimensions	1.0" H x 2.4" W x 2.3" D 2.5 cm H x 6.1 cm W x 5.8 cm D
Product weight	0.2 lbs (0.1 kg)
Shipping weight	1 lbs (1 kg)
Vibration	ISTA 1A in carton (International Safe Transit Association)
Listings	UL, CUL
Compliances	CE, FCC Class A, VCCI, AS/NZS, ICES
MTBF	30,000 hours
Warranty	3 years parts and labor

NOTE *All nominal levels are at ±10%.*

NOTE *Specifications are subject to change without notice.*

(7.51-122104-D1)